

이진 탐색 (Binary Search)

※ Data가 정렬이 되어 있어야 한다!

Algorithm,, Search

- 일반적 구현

```
public static int binarySearch(int[] arr, int target) {
    int left = 0;
    int right = arr.length - 1;
    int mid = 0;
    while(left <= right) {
        mid = (left + right) / 2;
        if(arr[mid] < target)
            left = mid + 1;
        else if (arr[mid] > target)
            right = mid - 1;
        else
            return mid;
    }
    return Integer.MIN_VALUE;
}
```

- 재귀적 구현

```
public static int binarySearchRecursive(int[] arr, int target, int left,
int right) {
    if(left > right)
        return Integer.MIN_VALUE;
    int mid = (left + right) / 2;
    if(arr[mid] < target)
        return binarySearchRecursive(arr, target, left + 1, right);
    else if (arr[mid] > target)
        return binarySearchRecursive(arr, target, left, right - 1);
    else
        return mid;
}
```

Interpolation Search (보간 탐색)

중간부터 찾지 말고, 실제 값이 있는 위치부터 찾기!

- 일반적 구현

```

public static int interpolationSearch(int[] arr, int target) {
    int left = 0;
    int right = arr.length - 1;
    int mid = 0;
    int count = 0;
    while(left <= right) {
        mid = (int)((double)target - arr[left]) / (arr[right] -
arr[left]) * (right - left) + left);
        if(arr[mid] < target)
            left = mid + 1;
        else if (arr[mid] > target)
            right = mid - 1;
        else {
            System.out.println(count);
            return mid;
        }
        count++;
    }
    return Integer.MIN_VALUE;
}

```

- 재귀적 구현

```

public static int interpolationSearchRecursive(int[] arr, int target,
int left, int right) {
    if(arr[left] > target || arr[right] < target) // 값의 범위를 넘어서는 경
우 있음.
        return Integer.MIN_VALUE;
    int mid = (int)((double)target - arr[left]) / (arr[right] -
arr[left]) * (right - left) + left);
    if(arr[mid] < target)
        return interpolationSearchRecursive(arr, target, left + 1,
right);
    else if (arr[mid] > target)
        return interpolationSearchRecursive(arr, target, left, right -
1);
    else
        return mid;
}

```

- $A \leq X \leq B$ 조건을 검색. (반환값이 index+1 이므로)

첫번째 값을 찾지 못하는 Bug 있음.

// 보간탐색을 이용한 근사값 찾기

```

public static int interpolationSearch(char[] arr, int left, int right,

```

```
int target) {
    int mid = 0;
    while(left <= right) {
        mid = (int)(((double)target - arr[left]) / (arr[right] -
arr[left]) * (right - left) + left);

        // index가 left보다 크고, right보다 작을 때
        if(mid > left && mid < right) {
            if(arr[mid - 1] < target && target <= arr[mid]) {
                return mid + 1;
            }
        }
        else if (mid == left) {
            return left + 1;
        }
        else
            return Integer.MIN_VALUE;

        if(arr[mid] < target)
            left = mid + 1;
        else if (arr[mid] > target)
            right = mid - 1;
    }
    return Integer.MIN_VALUE;
}
```

From:

<http://wiki.ledyx.xyz/> - **Ledyx WIKI**

Permanent link:

http://wiki.ledyx.xyz/doku.php?id=algorithm:binary_search

Last update: **2021/02/07 03:15**

