**Regular Expression**

Tips, Java

Java에서 아래와 같은 구문으로 이용한다.

```
Pattern p = Pattern.compile("^REGULAR_EXPRESSION$",
Pattern.CASE_INSENSITIVE); // regex, pattern
Matcher m = p.matcher(STRING);
boolean b = m.matches();
```

**Java 전용 표현**

https://docs.oracle.com/javase/7/docs/api/java/util/regex/Pattern.html

**Pattern Constant**

```
Pattern.CASE_INSENSITIVE    (?i)
Pattern.COMMENTS            (?x)
Pattern.MULTILINE           (?m)
Pattern.DOTALL              (?s)
Pattern.LITERAL             None
Pattern.UNICODE_CASE        (?u)
Pattern.UNIX_LINES          (?d)
```

**POSIX character classes (US-ASCII only)**

```
p{Lower}    A lower-case alphabetic character: [a-z]
p{Upper}    An upper-case alphabetic character:[A-Z]
p{ASCII}    All ASCII:[\x00-\x7F]
p{Alpha}    An alphabetic character:[\p{Lower}\p{Upper}]
p{Digit}    A decimal digit: [0-9]
p{Alnum}    An alphanumeric character:[\p{Alpha}\p{Digit}]
p{Punct}    Punctuation: One of !"#$%&'()*+,-./:;<=>?@[\]^_`{|}~
p{Graph}    A visible character: [\p{Alnum}\p{Punct}]
p{Print}    A printable character: [\p{Graph}\x20]
p{Blank}    A space or a tab: [ \t]
p{Cntrl}    A control character: [\x00-\x1F\x7F]
p{XDigit}   A hexadecimal digit: [0-9a-fA-F]
p{Space}    A whitespace character: [ \t\n\x0B\f\r]
```

**활용**

**전화번호**

```
^(02|0[3-6]{1}[1-5]{1})-?[0-9]{3,4}-?[0-9]{4}$ //지역번호-xxx(x)-xxxx
^(15(44|77|88|99)|1644)-?[0-9]{4}$ //15xx/1644-xxxx
```

**소괄호 안 문자( Parameter) 추출**

```
String str = "(int a, int b)";

Pattern p = Pattern.compile("\\((.*?)\\)");
Matcher m = p.matcher(str);

while(m.find())
    System.out.println(m.group(1));
```

From:
https://wiki.ledyx.xyz/ - **Ledyx WIKI**

Permanent link:
**https://wiki.ledyx.xyz/doku.php?id=regular_expression&rev=1665838213**

Last update: **2026/10/24 07:03**